

## New MIN 2500-6000TL-X Model is Coming

Growatt will have a new EU model MIN 2500-6000TL-X, which will take the place of the model MIN 2500-6000TL-XE in EU countries from Q3-Q4, 2022. MIN 2500-6000TL-X is the globally universal model name for MIN series, to which EU model MIN 2500-6000TL-XE will change. These 2 models are with the same specifications, interfaces, also same functions. Here are the key parameters of MIN 3600TL-X and MIN 3600TL-XE for example:

Model	MIN 3600TL-X	MIN 3600TL-XE
Max. DC voltage	550V	550V
MPPT voltage	80-550V	80-550V
No. of MPPT /string per MPPT	2/1	2/1
Max. input current per MPPT	13.5A	13.5A
AC normal power	3600W	3600W
Max. AC apparent power	3600VA	3600VA
Max. AC current	16A	16A
DC/AC surge protection	Type II/Type III	Type II/Type III
AFCI protection	Yes	Optional
Dimensions(W/H/D)	375/350/160mm	375/350/160mm
Weight	10.8kg	10.8kg
Cooling	Natural	Natural
DC connection	H4/MC4(optional)	H4/MC4(optional)
AC connection	Connector	Connector
Display	OLED+LED	OLED+LED
Interfaces	RS485, USB	RS485, USB
Monitor options	WiFi/GPRS/RF/ LAN	WiFi/GPRS/RF/ LAN
Warranty	10 years	10 years